

AD-770 768

SECURE COMPUTER SYSTEMS: MATHEMATICAL  
FOUNDATIONS

D. Elliott Bell, et al

Mitre Corporation

Prepared for:

Electronics Systems Division

November 1973

DISTRIBUTED BY:

**NTIS**

National Technical Information Service  
U. S. DEPARTMENT OF COMMERCE  
5285 Port Royal Road, Springfield Va. 22151

SECURE COMPUTER SYSTEMS: MATHEMATICAL FOUNDATIONS

D. E. Bell  
L. J. LaPadula

NOVEMBER 1973

Prepared for  
DEPUTY FOR COMMAND AND MANAGEMENT SYSTEMS

ELECTRONIC SYSTEMS DIVISION  
AIR FORCE SYSTEMS COMMAND  
UNITED STATES AIR FORCE  
L. G. Hanscom Field, Bedford, Massachusetts



Reproduced by  
NATIONAL TECHNICAL  
INFORMATION SERVICE  
U S Department of Commerce  
Springfield VA 22151

Approved for public release;  
distribution unlimited.

Project 522B  
Prepared by  
THE MITRE CORPORATION  
Bedford, Massachusetts  
Contract No. F19628-73-C-0001

AD 770768

When U.S. Government drawings, specifications, or other data are used for any purpose other than a definitely related government procurement operation, the government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise, as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Do not return this copy. Retain or destroy.

**REVIEW AND APPROVAL**

Publication of this technical report does not constitute Air Force approval of the report's findings or conclusions. It is published only for the exchange and stimulation of ideas.



MELVIN B. EMMONS, Colonel, USAF  
Director, Information Systems Technology  
Deputy for Command & Management Systems

1a

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER ESD-TR-73-276, Vol. I	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) SECURE COMPUTER SYSTEMS: MATHEMATICAL FOUNDATIONS		5. TYPE OF REPORT & PERIOD COVERED
7. AUTHOR(s) D. E. Bell, L. J. LaPadula		6. PERFORMING ORG. REPORT NUMBER MTR-2547, Vol. I
9. PERFORMING ORGANIZATION NAME AND ADDRESS The MITRE Corporation Box 206 Bedford, Mass. 01730		8. CONTRACT OR GRANT NUMBER(s) F19628-73-C-0001
11. CONTROLLING OFFICE NAME AND ADDRESS Deputy for Command and Management Systems Electronics Systems Division, AFSC L. G. Hanscom Field, Bedford, Mass. 01730		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS Project 522B
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		12. REPORT DATE NOVEMBER 1973
		13. NUMBER OF PAGES 36 41
		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/CONTINUING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) MATHEMATICAL MODELS MULTI-LEVEL SYSTEMS SECURE COMPUTER SYSTEMS		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) This paper reports the first results of an investigation into solutions to problems of security in computer systems; it establishes the basis for rigorous investigation by providing a general descriptive model of a computer system. Borrowing basic concepts and constructs from general systems theory, we present		

a basic result concerning security in computer systems, using precise notions of "security" and "compromise". We also demonstrate how a change in requirements can be reflected in the resulting mathematical model.

A lengthy introductory section is included in order to bridge the gap between general systems theory and practical problem solving.

## FCREWORD

This is Volume I of a multi-volume report prepared by The MITRE Corporation, Bedford, Massachusetts, in support of Project 522B under Contract No. F19628-73-C-0001.

The authors of the report are D. Elliott Bell and Leonard J. LaPadula of the MITRE Corporation.

This report represents an initial attempt at specifying requirements for a secure computer system based upon the development and verification of a mathematical model.

The assumptions and specifications relating to security requirements as expressed in the report are not necessarily applicable to any specific system. The development presented here will help to reveal and clarify the basic problems and issues confronting designers of multi-level secure computer systems.

## PREFACE

General systems theory is a relatively new and rapidly growing mathematical discipline which shows great promise for application in the computer sciences. The discipline includes both "general systems-theory" and "general-systems theory": that is, one may properly read the phrase "general systems theory" in both ways.

In this paper, we have borrowed from the works of general systems theorists, principally from the basic work of Mesarović, to formulate a mathematical framework within which to deal with the problems of secure computer systems. At the present time we feel that the mathematical representation developed herein is adequate to deal with most if not all of the security problems one may wish to pose. In Section III we have given a result which deals with the most trivial of the secure computer systems one might find viable in actual use. In the concluding section we review the application of our mathematical methodology and suggest major areas of concern in the design of a secure system.

The results reported in this paper lay the groundwork for further, more specific investigation into secure computer systems. The investigation will proceed by specializing the elements of the model to represent particular aspects of system design and operation. Such an investigation will be reported in the second volume of this series where we assume a system with centralized access control. A preliminary investigation of distributed access is just beginning; the results of that investigation would be reported in a third volume of the series.

## TABLE OF CONTENTS

	<u>Page</u>
LIST OF TABLES	vi
SECTION I INTRODUCTION	1
GENERAL SYSTEMS	1
SYSTEM MODELING	6
SECURE COMPUTER SYSTEMS	9
PROBLEMS OF SECURITY	10
SUMMARY AND REFERENCES	10
SECTION II FOUNDATIONS OF A MATHEMATICAL MODEL	14
ELEMENTS OF THE MODEL	14
STATES OF THE SYSTEM	17
STATE-TRANSITION RELATION	17
SUMMARY AND REFERENCES	18
SECTION III A FUNDAMENTAL RESULT	19
COMPROMISE AND SECURITY	19
ASSUMPTIONS	20
BASIC SECURITY THEOREM	21
SUMMARY	22
SECTION IV CONCLUSION	23
INTRODUCTION	23
PROBLEM REFORMULATION	24
Basic Security Theorem (revised)	25
ACCESS CONTROL	27
DATA BASE SHARING	28
SUMMARY AND REFERENCES	29
BIBLIOGRAPHY	31



## LIST OF TABLES

<u>Table Number</u>		<u>Page</u>
I	State-Transition Table	5
II	Elements of the Model	14
III	Initial Requirements	20
IV	Modified Requirements	25

## SECTION I

### INTRODUCTION

#### GENERAL SYSTEMS

We shall begin by presenting a brief description of general systems theory as we shall use it in this paper. We consider a system in its most general form to be a relation on abstract sets. We express this mathematically by the expression

$$S \subseteq X \times Y$$

where the system  $S$  is a relation on the abstract sets  $X$  and  $Y$ . If  $S$  is a function from  $X$  to  $Y$  ( $S: X \rightarrow Y$ ), then it is natural to consider  $S$  to be a functional system. In this case, it is convenient to consider the elements of  $X$  to be inputs and the elements of  $Y$  to be outputs so that  $S$  expresses a functional input-output relationship. By appropriate choice of the sets  $X$  and  $Y$  (and a set  $Z$  to represent states when necessary), one can closely represent some situation of particular interest and reach significant conclusions about that situation.

This very general definition of a system provides a framework of investigation which has very wide applicability and, as we shall see in Section III, unexpected power. We shall illustrate the concept's applicability with three examples.

Example 1: Consider a savings account in a bank which compounds interest quarterly. The general situation of varying payments, withdrawals, and interest rates can be described by a difference

equation as follows:

$$b_k = (b_{k-1} + p_k) \cdot (1 + i_k) \quad (1.1)$$

where  $b_k$  represents the balance after the computation of interest at the end of the  $k$ -th quarter,  $p_k$  represents the net transaction (that is, the net of deposits and withdrawals) in the account during the  $k$ -th quarter,\* and  $i_k$  represents the quarterly interest rate at the end of the  $k$ -th quarter. A seven-year history of such a savings account (seven years for tax purposes) is represented by a system

$$S(b_0) \subseteq P \times I \times B$$

where

$b_0$  represents the initial balance in the account;  
 $P = R^{28\dagger}$  represents the twenty-eight transactions;  
 $I = R^{28}$  represents the twenty-eight quarterly interest rates;  
 and  $B = R^{28}$  represents the twenty-eight successive balances

and  $(p, i, b) \in S(b_0)$  if and only if equation (1.1) holds for every  $k$  from 1 to 28 inclusive, where  $p = (p_1, \dots, p_{28})$ ;  $i = (i_1, \dots, i_{28})$ ; and  $b = (b_1, \dots, b_{28})$ . The system  $S(b_0)$  describes in full generality the seven-year savings-account history in any circumstance. Certain results in econometrics are equivalent to determining  $b_{28}$  under further specific assumptions. For example, the determination of  $b_{28}$  for  $(p, i, b) \in S(0)$  where  $p_2 = \dots = p_{28} = 0$  and  $i_1 = i_2 = \dots = i_{28} > 0$  is accomplished using the

---

\*We assume for simplicity that interest is paid on the amount in the account at the end of the quarter.

†The set of 28-tuples of real numbers.

compound interest formula

$$b_{28} = p_1 \cdot (1 + i_1)^{28}.$$

A number of remarks concerning this example are in order. It is certainly true that the use of an econometric table prepared for a specific situation is easier than the direct use of the difference equation (1.1). On the other hand, small changes in a situation can make the use of tables cumbersome. For example, suppose that the  $p_j$  in the sequence  $(p_1, p_2, \dots, p_{28})$  are positive and distinct and that  $i_1 = i_2 = \dots = i_{28} > 0$ . Then by use of econometric tables, we compute  $b_{28}$  by the formula

$$b_{28} = \sum_{j=1}^{28} p_j \cdot (F/P, i_1, 29 - j).^*$$

This means that the compound amount factor  $(F/P, i_1, 29 - j)$  must be looked up 28 times in the compound interest factors table one is using. If we further complicate the problem by having the  $i_j$  in  $(i_1, i_2, \dots, i_{28})$  distinct and positive, then we could compute  $b_{28}$  by the iterative method:

$$\begin{aligned} b_{28} &= (b_{27} + p_{28}) \cdot (F/P, i_{28}, 1) \\ b_{27} &= (b_{26} + p_{27}) \cdot (F/P, i_{27}, 1) \\ &\cdot \\ &\cdot \\ &\cdot \\ b_1 &= (b_0 + p_1) \cdot (F/P, i_1, 1); \end{aligned}$$

or we could use the single formula obtainable by straightforward algebraic substitution in the equations above. So, to find  $b_{28}$ ,

---

\*See [5], page 594.

we start with  $b_0$  and work backwards; in using the compound interest factors tables we should have to do 28 look-ups, each on a different page since in each quarter the interest is different from that in any other quarter. If it happens that each  $i_j < k\%$ , where  $k\%$  is the lowest interest for which we have a table, our problem has become even more severe. It is much easier in these cases, especially on a digital computer, simply to use the difference equation (1.1).

The preceding remarks should illustrate that the most important characteristics of the system (that is, the difference equation) are its appropriateness to the situation modeled and its general applicability.

Example 2: Consider the motion of a body  $B$  suspended on an ideal spring. The motion is governed by the differential equation

$$m \cdot s''(t) + k \cdot s(t) = x(t) \quad (1.2)$$

where  $m$  is the mass of  $B$ ,  $s(t)$  is the position of  $B$  at time  $t$ ,  $k$  is a constant of the spring, and  $x(t)$  is an external force acting on  $B$  at time  $t$ . If  $C$  is the set of all analytic functions on  $[0, \infty)$ , then the differential equation (1.2) with initial conditions  $s(0) = a$  and  $s'(0) = b$  is represented by the system  $S(a, b)$  defined as follows:

$$S(a, b) \subseteq C \times C$$

where  $(x(t), s(t)) \in S(a, b)$  if and only if  $s(0) = a$ ,  $s'(0) = b$ , and the functions  $x$  and  $s$  satisfy (1.2) for all  $t \in [0, \infty)$ . Hence the familiar analytical tool of differential equations is a

system under our very broad definition. Our third example will show that finite-state machines are also encompassed in our concept of system.

Example 3: Consider a vending machine which accepts nickels, dimes, and quarters for a ten-cent cup of coffee and gives change if any is due. Let  $A = \{5, 10, 25\}$  represent the coins acceptable to the machine. Let  $B_1 = \{\phi, C\}$  where " $\phi$ " means "no coffee" and "C" means "coffee". Let  $B_2 = \{0, 5, 10, 25\}$  represent the coins the machine can return. The set  $B = B_1 \times B_2 \times B_2$  specifies the set of outputs that can occur at any time. Now let the set  $Q = \{q_0, q_1\}$  represent the states of the machine. We give a state transition function  $f: A \times Q \rightarrow Q$  and an output function  $g: A \times Q \rightarrow B$  by the following table:

Table I  
State-Transition

	a = 5	a = 10	a = 25		a = 5	a = 10	a = 25
$f(a, q_0)$	$q_1$	$q_0$	$q_0$	$g(a, q_0)$	$(\phi, 0, 0)$	$(C, 0, 0)$	$(C, 5, 10)$
$f(a, q_1)$	$q_0$	$q_0$	$q_1$	$g(a, q_1)$	$(C, 0, 0)$	$(C, 5, 0)$	$(\phi, 0, 25)$

We have now modeled the vending machine as a finite-state machine in the usual manner.

Now suppose that we observe  $n$  trials. Let  $A^n$  and  $B^n$  be, respectively, the sets of all  $n$ -tuples from the sets  $A$  and  $B$ . Then for a given initial state  $q = q_i$ ,  $i \in \{0, 1\}$ , there corresponds

to any input tape  $x$  in  $A^n$  a unique output tape  $y$  in  $B^n$ . We have defined a mapping

$$S_q : A^n \rightarrow B^n$$

such that for each  $x$  in  $A^n$  the image  $y = S_q(x)$  is the unique output sequence corresponding to the input sequence  $x$  and the initial state  $q = q_1$ . We say that the vending machine is represented by the system  $S \subseteq A^n \times B^n$  where  $S = S_{q_0} \cup S_{q_1}$ .

Considering that in normal operation of the machine the initial state is  $q_0$ , we can consider the vending machine to be the functional system  $S_{q_0}$ .

The examples we have presented are intended to enhance the intelligibility of the discussion of system modeling in the next section. Additionally, the enrichment of one's intuitive notions through the use of examples will, hopefully, serve a similar purpose in the next section.

#### SYSTEM MODELING

The mathematics of relations among objects with which we deal is designed to provide a useful model for our investigation of secure computer systems. Three desirable properties of such a model suggested by the examples of the previous section are generality, a predictive ability, and appropriateness. In this section, we shall discuss each of these properties in turn, commenting on its relation to a "useful" model of a particular situation.

Differential equations are systems that frequently display great generality. Equation (1.2) illustrates this point clearly.

Without knowing the mass of B and without specifying the spring constant k, we can nevertheless analyze the general system. In fact, for  $x(t) \equiv 0$ , (1.2) has the closed form solution

$$s(t) = A \cdot \sin(nt + C), \quad (1.3)$$

where  $n = (k/m)^{1/2}$  and A and C are constants determined by the initial conditions a and b. Moreover, equation (1.2) is a special case of the more general form

$$s''(t) + 2k \cdot s'(t) + n^2 \cdot s(t) = x(t)$$

which models a vast number of elastic vibrations including electrical oscillations (as in a capacitor) and the vibrations in pipe organs [2].

A model too closely tied to a specific application loses the possibility of more general applicability. On the other hand, a model insufficiently rooted in the problem at hand will not allow accurate prediction of the behavior of the physical system being modeled. For example, knowing the initial conditions of the suspended weight B, the mass of B, and the spring constant d, we can predict precisely where B will be 5.83337 seconds from "let-go." The same sort of precise predictive power is desirable in modeling discrete computer systems. Moreover, in modeling secure computer systems we must deny ourselves the luxury of accepting approximate answers and insist on absolute rather than probabilistic determinacy.

The last important feature of a model is its appropriateness to the situation of interest. In each of the three examples of Section I, the type of system used appropriately described the important properties of the situation being modeled. One particular



advantage of an appropriate model can be illustrated by the third example, while the severe problems which an inappropriate model can cause can be demonstrated by a discussion of the second example.

The vending machine modeled in Example 3 illustrates that problems other than correctness can be detected in a model appropriate to a given situation. In particular, the machine we have defined has this interesting characteristic: if in state  $q_1$  one continually inserts quarters into the machine, the machine monotonously returns a quarter and gives no coffee. This is a behavioral characteristic which the vending machine company might consider undesirable. We have purposely constructed our sample machine in this way in order to show that while the machine is "correct" in its operation, we may consider it to be non-viable as a profit-making item.\*

Now consider the situation modeled in Example 2. If a discrete model had been chosen over a continuous one, the model might have been represented by discrete observations of the spring-weight tandem

$$u_t = s(t), \quad t = 0, 1, 2, 3, \dots \quad (1.4)$$

where  $s(t)$  is the same position function appearing in (1.2). Suppose  $B$  has mass = 1 gram, the time interval is 1 second, and the spring constant is  $k = 39.478 \text{ g/sec}^2$ . In this special case, the motion of  $B$  indicates no apparent movement--the body  $B$  is always the same position ( $s(0)$ ) at each observation time. The

---

\*This characteristic (i.e., returning quarters inserted after a single nickel has been put into the machine) is one which might irritate customers and not sell coffee in the process. An alternative approach which, although not correct, might be more acceptable to a vending machine company would be to set  $f(25, q_1) = q_0$  and  $g(25, q_1) = (C, 5, 10)$ : that is, make change for the quarter, supply coffee, and ignore the nickel. Purposefully or inadvertently, this may well be the course chosen by some vending machine companies.

periodicity of E's motion is precisely what makes a continuous differential-equation model more appropriate than a discrete model of the type described (in addition to the more accurate predictive power). The point is that an inappropriate model of a problem situation can obfuscate the essential issues involved, thus complicating the problem.

The major task in system modeling is to provide a useful model of the situation under scrutiny, a model which exhibits generality, a predictive ability, and appropriateness to the problem at hand.

#### SECURE COMPUTER SYSTEMS

A number of systems have been built and designed which attack the general problem of security in some form and to some extent. In some cases, privacy of data is the principal objective; in others, the prime objective is access control. For the security criteria which we shall establish, however, no existing system of which we are aware is adequate. \*

When we speak of a secure computer system, we mean one which satisfies some definition of "security". Our interest is security in the usual military and governmental senses -- that is, security involving classifications and needs-to-know.

We shall investigate a bounded form of the general problem of security. Our interest shall be to certify that within the digital computer, which is only part of a total system, no security compromise will occur. The elements with which we shall deal, then, are processes (programs in execution), data, access control algorithms, classifications of data and processes, and the needs-to-know of elements within the digital computer.

---

\*See reference [13] at the end of this section.

## PROBLEMS OF SECURITY

Let us consider a security compromise to be unauthorized access to information, where unauthorized means that an inappropriate clearance or a lack of need-to-know is involved in the access to the information. Then a central problem to be solved within the computing system is how to guarantee that unauthorized access (by a process) to information (file, program, data) does not occur.

If we can certify that unauthorized access cannot occur within the system, then we must next consider the secondary effects of the method by which security has been achieved. Principally we shall have to address ourselves to the general question of the viability of the resultant system in terms of economic and technological feasibility and in terms of usefulness to the user.

## SUMMARY AND REFERENCES

In this chapter we have introduced general systems theory very briefly and have shown examples of its application. Together with the short discussion on system modeling, the general systems theory and examples should provide an adequate basis for reading the rest of this paper.

The reader who may wish to investigate systems theory for himself is referred first to the book edited by Klir [9], which can profitably be read with or without any background in mathematics. The reader will find further examples of systems in the book [14] by Mesarović, Macko, and Takahara. In particular, beginning on page 69 of [14] the reader will find the basic mathematical concept of a system which we have borrowed. Other books which should be of interest are those by Klir [8], Hammer [6], von Bertalanffy [1], and Zadeh and Polak [15].

In the section entitled SECURE COMPUTER SYSTEMS we defined in broad terms what we mean by a secure computer system. Our general notion of a secure system is derived in large measure from essentials of a secure system abstracted from the Multics system, as an archetype of multi-user systems, and from a knowledge of security problems. The reader can find numerous articles in the literature which touch on the area of a secure computer system; we list [3,4,10,11,12] as representative of what is available. As we pointed out, however, none of the generally available literature deals specifically with the problem we address in this paper.

Finally, we have indicated in this chapter what we consider to be the general problems we shall encounter in investigating secure computer systems.

1. von Bertalanffy, Ludwig., General System Theory, George Braziller, Inc., New York, 1968.
2. Ford, Lester R., Differential Equations, McGraw-Hill Book Company, New York, 1955.
3. Graham, G. Scott, and Peter J. Denning, "Protection - Principles and practice (sic)," AFIPS Conf. Proc. 40 Spring Joint Computer Conference 1972, pp. 417-429.
4. Graham, R.M. "Protection in an information processing utility," Comm ACM, 15 May 1968, pp. 365-369.

5. Grant, E. L., and W. G. Iveson, Principles of Engineering Economy, The Ronald Press Company, New York, 1970.
6. Hammer, Preston C., ed., Advances in Mathematical Systems Theory, Pennsylvania State University Press, University Park, Pennsylvania, 1969.
7. Hoffman, L. J., "Computers and privacy: a survey," Computing Surveys, 1, 2 June, 1969, pp. 85-104.
8. Klir, George J., An Approach to General Systems Theory, van Nostrand Reinhold Company, 1969.
9. Klir, George J., ed., Trends in General Systems Theory, Wiley-Interscience, New York, 1972.
10. Lampson, B. W., "Dynamic protection structures," AFIPS Conf. Proc. 35, Fall Joint Computer Conference 1969, pp. 27-38.
11. Lampson, B. W., "On reliable and extendable operating systems," Techniques in software engineering, NATO Science Committee Working Material Vol. II, September, 1969.
12. Lampson, B. W., "Protection," Proc. Fifth Annual Princeton Conf. on Inf. Sciences and Systems, Dept. of E. E., Princeton University, Princeton, N. J., March, 1971, pp. 437-443.

13. Lipner, Steven B., "Computer Security Research and Development Requirements", MTP-142, March 1973.
14. Mesarović, M. D., D. Macko, and Y. Takahara, Theory of Hierarchical, Multilevel, Systems, Academic Press, New York, 1970.
15. Zadeh, L. A., and E. Polak, System Theory, McGraw-Hill Book Company, New York, 1969.

## SECTION II

### FOUNDATIONS OF A MATHEMATICAL MODEL

#### ELEMENTS OF THE MODEL

We begin by identifying elements of the model which correspond to parts of the real system to be modeled. We assume the real system to have multiple users operating concurrently on a common data base with multi-level classification for both users and data and need-to-know categories associated with both users and data. In our model we deal with subjects (processes), which one should consider surrogates for the users.

We show the elements of our model in Table II, wherein we identify sets, elements of the sets, and an interpretation of the elements of the sets.

Table II

Elements of the Model

Set	Elements	Semantics
S	$\{S_1, S_2, \dots, S_n\}$	<u>subjects</u> ; processes, programs in execution
O	$\{O_1, O_2, \dots, O_m\}$	<u>objects</u> ; data, files, programs, subjects
C	$\{C_1, C_2, \dots, C_q\}$ $C_1 > C_2 > \dots > C_q$	<u>classifications</u> ; clearance level of a subject, classification of an object
K	$\{K_1, K_2, \dots, K_r\}$	<u>needs-to-know categories</u> ; project numbers, access privileges

Table II (Continued)

Set	Elements	Semantics
A	$\{A_1, A_2, \dots, A_p\}$	<u>access attributes</u> ; read, write, copy, append, owner, control
R	$\{R_1, R_2, \dots, R_u\}$	<u>requests</u> ; inputs, commands, requests for access to objects by subjects
D	$\{D_1, D_2, \dots, D_v\}$	<u>decisions</u> ; outputs, answers, "yes", "no", "error"
T	$\{1, 2, \dots, t, \dots\}$	<u>indices</u> ; elements of the time set; identification of discrete moments; an element $t$ is an index to request and decision sequences
$P\alpha$	all subsets of $\alpha$	<u>power set of <math>\alpha</math></u>
$\alpha^\beta$	all functions from the set $\beta$ to the set $\alpha$	-----
$\alpha \times \beta$	$\{(a, b) : a \in \alpha, b \in \beta\}$	<u>Cartesian product of the sets <math>\alpha</math> and <math>\beta</math></u>
F	$C^S \times C^O \times (PK)^S \times (PK)^O$ an arbitrary element of F is written $f = (f_1, f_2, f_3, f_4)$	<u>classification/need-to-know vectors</u> ;  $f_1$ : subject-classification function $f_2$ : object-classification function $f_3$ : subject-need-to-know function $f_4$ : object-need-to-know function



Table II (Concluded)

Set	Elements	Semantics
X	$R^T$ an arbitrary element of X is written $x$	<u>request sequences</u>
Y	$D^T$ an arbitrary element of Y is written $y$	<u>decision sequences</u>
M	$\{M_1, M_2, \dots, M_{nm2^p}\}$ an element $M_k$ of M is an $n \times m$ matrix with entries from PA; the (i,j)-entry of $M_k$ shows $S_i$ 's access attributes relative to $O_j$	<u>access matrices</u>
V	$P(S \times O) \times M \times F$	<u>states</u>
Z	$V^T$ an arbitrary element of Z is written $z$ ; $z_t \in z$ is the t-th state in the state sequence $z$	<u>state sequences</u>

### STATES OF THE SYSTEM

We have defined the states of the system in such a way as to embody all the information which we consider pertinent to security considerations.

A state  $v \in V$  is a 3-tuple  $(b, M, f)$  where

$b \in P(S \times O)$ , indicating which subjects have access to which objects in the state  $v$ ;  
 $M \in M$ , indicating the entries of the access matrix in the state  $v$ ; and  
 $f \in F$ , indicating the clearance level of all subjects, the classification level of all objects, and the needs-to-know associated with all subjects, and objects in the state  $v$ .

### STATE-TRANSITION RELATION

Let  $W \subseteq R \times D \times V \times V$ . The system  $\Sigma(R, D, W, z_0) \subseteq X \times Y \times Z$  is defined by

$(x, y, z) \in \Sigma(R, D, W, z_0)$  if and only if  $(x_t, y_t, z_t, z_{t-1}) \in W$  for each  $t \in T$ , where  $z_0$  is a specified initial state usually of the form  $(\phi, M, f)$ , where  $\phi$  denotes the empty set.

$W$  has been defined as a relation. It can be specialized to be a function, although this is not necessary for the development herein. When considering design questions, however,  $W$  will be a function, specifying next-state and next-output.  $W$  should be considered

intuitively as embodying the rules of operation by which the system in any given state determines its decision for a given request and moves into a next state.

#### SUMMARY AND REFERENCES

In this section we have established elements of a mathematical model of a system; these elements were chosen to represent as nearly as possible the realities of the problem situation and to enable as easy a transition as possible from mathematical model to design specifications.

The states of the system have been defined in such a way as to incorporate all information which seems pertinent to correct operation of a secure system ("secure system" to be defined precisely in the next section).

Finally, we have included in the model a state-transition relation  $W$  which is the key to modeling: given  $W$  one may predict the behavior of the system for a given set of initial conditions and a given request sequence.

### SECTION III

#### A FUNDAMENTAL RESULT

##### COMPROMISE AND SECURITY

We define a compromise state as follows:  $v = (b, M, f) \in V$  is a compromise state (compromise) if there is an ordered pair  $(S, O) \in b$  such that

$$(i) \quad f_1(S) < f_2(O) \text{ or}$$

$$(ii) \quad f_3(S) \not\geq f_4(O).$$

In other words,  $v$  is a compromise if the current allocation of objects to subjects  $(b)$  includes an assignment  $((S, O))$  with at least one of two undesirable characteristics:

(i')  $S$ 's clearance is lower than  $O$ 's classification;

(ii')  $S$  does not have some need-to-know category that is assigned to  $O$ .

In order to make later discussions and arguments a little more succinct, we shall define a security condition.  $(S, O) \in S \times O$  satisfies the security condition relative to  $f$  (SC rel  $f$ ) if

$$(iii) \quad f_1(S) \geq f_2(O) \text{ and}$$

$$(iv) \quad f_3(S) \geq f_4(O).$$

A state  $v = (b, M, f) \in V$  is a secure state if each  $(S, O) \in b$  satisfies SC rel  $f$ . The definitions of secure states and compromise states indicate the validity of the following unproved proposition.

Proposition:  $v \in V$  is not a secure state iff  $v$  is a compromise.

A state sequence  $z \in Z$  has a compromise if  $z_t$  is a compromise for some  $t \in T$ .  $z$  is a secure state sequence if  $z_t$  is a secure state for each  $t \in T$ . We shall call  $(x, y, z) \in \Sigma(R, D, W, z_0)$  an appearance of the system.  $(x, y, z) \in \Sigma(R, D, W, z_0)$  is a secure appearance if  $z$  is a secure state sequence. The appearance  $(x, y, z)$  has a compromise if  $z$  has a compromise.

$\Sigma(R, D, W, z_0)$  is a secure system if every appearance of  $\Sigma(R, D, W, z_0)$  is secure.  $\Sigma(R, D, W, z_0)$  has a compromise if any appearance of  $\Sigma(R, D, W, z_0)$  has a compromise.

Proposition:  $z \in Z$  is not secure iff  $z$  has a compromise.

Proposition:  $\Sigma(R, D, W, z_0)$  is not secure iff  $\Sigma(R, D, W, z_0)$  has a compromise.

#### ASSUMPTIONS

We make assumptions, as shown in Table III, which reflect a subset of requirements (or lack of requirements) to be imposed on the system. In Section IV we shall change some of these assumptions and observe the effect on the system.

Table III  
Initial Requirements

	REQUIREMENTS	
	RAISE?	LOWER?
SUBJECT CLEARANCE	NO	NO
OBJECT CLASSIFICATION	NO	NO
	INCREASE?	DECREASE?
SUBJECT NEEDS-TO-KNOW	NO	NO
OBJECT NEEDS-TO-KNOW	NO	NO

Table III, in effect, says that "no" is the answer to each of the questions

"Is there a requirement to  $\left\{ \begin{array}{l} \text{raise} \\ \text{lower} \\ \text{increase} \\ \text{decrease} \end{array} \right\}$  a

$\left\{ \begin{array}{l} \text{subject's} \\ \text{object's} \end{array} \right\}$  .  $\left\{ \begin{array}{l} \text{classification/clearance} \\ \text{needs-to-know} \end{array} \right\}$  ?".

#### BASIC SECURITY THEOREM

Basic Security Theorem: Let  $W \subseteq R \times D \times V \times V$  be any relation such that  $(R_1, D_1, (b^*, M^*, f^*), (b, M, f)) \in W$  implies

- (i)  $f = f^*$  and
- (ii) every  $(S, O) \in b^* - b$  satisfies SC rel  $f^*$ .

$\Sigma(R, D, W, z)$  is a secure system for any secure state  $z$ .

Proof: Let  $z_0 = (b, M, f)$  be secure. Pick  $(x, y, z) \in \Sigma(R, D, W, z)$  and write  $z_t = (b^{(t)}, M^{(t)}, f^{(t)})$  for each  $t \in T$ .

$z_1$  is a secure state.  $(x_1, y_1, z_1, z) \in W$ . Thus by (i),  $f^{(1)} = f$ . By (ii), every  $(S, O)$  in  $b^{(1)} - b$  satisfies SC rel  $f^{(1)}$ . Since  $z$  is secure, every  $(S, O) \in b$  satisfies SC rel  $f$ . Since  $f = f^{(1)}$ , every  $(S, O) \in b^{(1)}$  satisfies SC rel  $f^{(1)}$ . That is,  $z_1$  is secure.

If  $z_{t-1}$  is secure,  $z_t$  is secure.  $(x_t, y_t, z_t, z_{t-1}) \in W$ .

Thus by (i),  $f^{(t)} = f^{(t-1)}$ . By (ii), every  $(S, O)$  in  $b^{(t)} - b^{(t-1)}$  satisfies SC rel  $f^{(t)}$ . Since  $z_{t-1}$  is secure, every  $(S, O) \in b^{(t-1)}$  satisfies SC rel  $f^{(t-1)}$ . Since  $f^{(t)} = f^{(t-1)}$ , every  $(S, O) \in b^{(t)}$  satisfies SC rel  $f^{(t)}$ . That is,  $z_t$  is secure. By induction,  $z$  is secure so that  $(x, y, z)$  is a secure appearance.  $(x, y, z)$  being arbitrary,  $\Sigma(R, D, W, z_0)$  is secure.

#### SUMMARY

In this chapter we have applied the mathematical model of Section II to the modeling of a secure computer system. We have defined a secure system precisely, through the definitions of security and compromise, and have given a rule of operation,  $W$ , which we have shown guarantees that the system is secure in its operation.

## SECTION IV

### CONCLUSION

#### INTRODUCTION

We attempted to provide in Section I a motivation and basis for the remainder of this paper. We pointed out three desirable properties of a model -- generality, predictive ability, and appropriateness -- and these were illustrated by example. Also, we discussed the general principle that the specificity of prediction is roughly proportional to the amount and level of detail of information available about the system being modeled; this was illustrated by the discussion of the spring-mass system.

Subsequently, we developed a mathematical model of general applicability to the study of secure computer systems, abstracting the elements of the model from our own and others' notions of what the real system may be like.

We then applied the model, under a given set of assumptions, to the question of security (compromise). We gave a rule by which, for the assumptions given, the system would remain secure in its operation; we also gave a proof of the last assertion.

Notice this important point: our proof did not depend on the choice of elements for the set  $A$  (access attributes). This means that any set is acceptable and any access matrix is acceptable. Stated differently, we have shown that under the given assumptions security of the system is independent of the access matrix and the rules (if any) by which the access matrix is changed.



Thus, we have modeled the system in such generality that we are not in a position to investigate its viability. For, clearly, one may arbitrarily choose rules of access matrix control while retaining the property of security. Therefore, one may choose the rules in such a way as to prevent users from ever acquiring access to information; the severe danger is that a set of rules might be chosen which has an intuitive sense of correctness but which may lead the system into undesirable states.

We shall address ourselves in this section to some of the specific questions to be considered if a viable system is to be developed from our model.

#### PROBLEM REFORMULATION

One may change the system problem to be attacked in a variety of ways. In general one states a set of requirements and a set of criteria to be met. The requirements and criteria may be very general or very specific: the more specific these are, the more specific can be the behavior predicted by modeling and the greater the probability that a viable system will result from the design into which the model is transformed.

In our situation we can immediately recognize two areas of problem reformulation. First, one may change the requirements of the type we assumed in Section III. We shall, in fact, do so and derive a result from the changed assumptions. Second, one may impose criteria to be met by the access control mechanisms of the system. We shall investigate this briefly in the next two sections.

We change the assumptions we made in Section III, as shown in Table IV.

Table IV  
Modified Requirements

	REQUIREMENTS	
	RAISE?	LOWER?
SUBJECT CLEARANCE	YES	NO
OBJECT CLASSIFICATION	NO	YES
	INCREASE?	DECREASE?
SUBJECT NEEDS-TO-KNOW	YES	NO
OBJECT NEEDS-TO-KNOW	NO	YES

Basic Security Theorem (revised):

Let  $W \subseteq R \times D \times V \times V$  be any relation such that

$(R_1, D_j, (b^*, M^*, f^*), (b, M, f)) \in W$  implies

- (i)  $f_1^*(S) \geq f_1(S)$  for each  $S \in S$ ,  
 $f_2^*(O) \leq f_2(O)$  for each  $O \in O$ ,  
 $f_3^*(S) \geq f_3(S)$  for each  $S \in S$ ,  
 $f_4^*(O) \leq f_4(O)$  for each  $O \in O$ , and
- (ii) every  $(S, O) \in b^* - b$  satisfies SC rel  $f^*$ .

Then  $\Sigma(R, D, W, z_0)$  is a secure system for any secure state  $z_0$ .

Proof: Let  $z_0 = (b, M, f)$  be secure.

Pick  $(x, y, z) \in \Sigma(R, D, W, z)$  and write  $z_t = (b^{(t)}, M^{(t)}, f^{(t)})$   
for each  $t \in T$ .

$z_1$  is a secure state.  $(x_1, y_1, z_1, z_0) \in W$ .

By (ii), every  $(S,0)$  in  $b^{(1)} - b$  satisfies SC rel  $f^{(1)}$ . Since  $z$  is secure, every  $(S,0)$  in  $b$  satisfies SC rel  $f$ ; that is,  $f_1(S) \geq f_2(0)$  and  $f_3(S) \geq f_4(0)$ . By (i), we have, for each  $(S,0)$  in  $b^{(1)} - (b^{(1)} - b)$ ,  $f_1^{(1)}(S) \geq f_1(S) \geq f_2(0) \geq f_2^{(1)}(0)$  and  $f_3^{(1)}(S) \geq f_3(S) \geq f_4(0) \geq f_4^{(1)}(0)$ , so that each  $(S,0)$  in  $b^{(1)}$  satisfies SC rel  $f^{(1)}$ . That is,  $z_1$  is secure.

If  $z_{t-1}$  is secure, then  $z_t$  is secure.

$(x_t, y_t, z_t, z_{t-1}) \in W$ . By (ii), every  $(S,0)$  in  $b^{(t)} - b^{(t-1)}$  satisfies SC rel  $f^{(t)}$ . Since  $z_{t-1}$  is secure, every  $(S,0)$  in  $b^{(t-1)}$  satisfies SC rel  $f^{(t-1)}$ ; that is,  $f_1^{(t-1)}(S) \geq f_2^{(t-1)}(0)$  and  $f_3^{(t-1)}(S) \geq f_4^{(t-1)}(0)$ . By (i), we have for each  $(S,0)$  in  $b^{(t)} - (b^{(t)} - b^{(t-1)})$ ,  $f_1^{(t)}(S) \geq f_1^{(t-1)}(S) \geq f_2^{(t-1)}(0) \geq f_2^{(t)}(0)$  and  $f_3^{(t)}(S) \geq f_3^{(t-1)}(S) \geq f_4^{(t-1)}(0) \geq f_4^{(t)}(0)$ , so that each  $(S,0)$  in  $b^{(t)}$  satisfies SC rel  $f^{(t)}$ . That is,  $z_t$  is secure.

By induction,  $z$  is secure so that  $(x,y,z)$  is a secure appearance.  $(x,y,z)$  being arbitrary,  $\Sigma(R,D,W,z_0)$  is secure.

The revised theorem just proved indicates that dynamic

- (i) raising of subject clearance;
- (ii) lowering of object classification;
- (iii) increasing of subject needs-to-know; and
- (iv) decreasing of object needs-to-know

can be provided in the system without security compromise. Again, however, the proof is independent of what is happening in the access matrix, the subject of the next section.

We note here that our investigations into the security of a system in the cases that a subject's clearance may be lowered dynamically, an object's classification may be increased dynamically, and similar changes in needs-to-know are as yet undocumented. Those investigations lead us to believe that severe questions of the viability of the resulting system are raised by the options listed above.

#### ACCESS CONTROL

In a real sense, the relation  $W$  we have specified provides a rule of access control which governs security as we have defined it. We have also provided in the model for access control to govern protection, privilege, and mode of use through the access matrix we have defined.

Two problems are immediately evident. First, unless the system guarantees the inviolability of rule  $W$  our security theorem does not apply. Second, unless we deal with some specific criteria and rules relating to the access matrix, we can say little if anything concerning viability of the system; again, if access matrix controls are provided, the system must be structured so as to guarantee their inviolability else our modeling will not apply.

Let us consider a situation in which the interaction of security control and access control can cause a compromise. Specifically, if a subject  $S_i$  is allowed "append" access to an object  $O_k$ , a file or segment, then guaranteeing inviolability of rule  $W$  means the system must prevent  $S_i$  from appending information of a classification higher than that of  $O_k$ : otherwise we risk having  $(S_i, O_k)$  in  $b$ , where  $S_j$  has "read" access to  $O_k$ , while  $f_1(S_j) < f_2(O_k)$  resulting in compromise. This example shows that inadequate access controls (over the "append" access of  $S_i$  to  $O_k$ ) can cause a violation of  $W$  (by raising  $f_2(O_k)$ , contrary to our assumption up to this point), resulting in a compromise state.

#### DATA BASE SHARING

We have assumed a shared data base for the multi-user system but have stated no requirements nor criteria for "correct" sharing. The concluding remark of the preceding section suggests that we must do so. At least, we must specifically prevent the situation we discussed; alternatively, one might choose to change our definition of compromise. Unfortunately, a change in the definition of compromise in this situation would be in the direction of weakening rule  $W$  with the result that the model will reflect the real problem less accurately than we have succeeded in doing thus far.

In addition, one may impose additional criteria relating to sharing of the data base, such as prevention of deadlock, preservation of integrity of the information, and prevention of permanent blocking--such criteria have to do with reliability of the system and therefore relate to its usefulness.

## SUMMARY AND REFERENCES

In this chapter we have discussed the generalities of changing the definition of the problem to be solved. We showed an example by stating and proving the security theorem for a new set of assumptions relating to changes in classifications and needs-to-know.

We pointed out briefly that the system which one might develop from our model would have to guarantee inviolability of the rule of operation W. Techniques have been documented which use hardware, software, or combinations of these for protection of privileged algorithms; references [1,2,3,4,5,6,8,9,10] are relevant.

We discussed briefly the question of a shared data base. For a discussion of problems and a solution see [7].

In summary, we have attempted to show in this section that the model can be used to answer questions posed with a given set of requirements and criteria and to indicate that a central problem in the design of a secure system will be to certify that the access controls are inviolable.

1. Conway, R., W. Maxwell, and H. Morgan, "Selective security capabilities in ASAP--A file management system," AFIPS Conf. Proc. 40, SJCC 1972.
2. Emerson, H., "An Approach to Handling Multi-Level Data Element Security Within a File," Proceedings Invitational Workshop on Networks of Computers, AD 860 776, October 1968.
3. Graham, R. M., "Protection in an information processing utility," Comm ACM, 15 May 1968, pp. 365-369.

4. Hoffman, L. J., "The Formulary Model for Access Control and Privacy in Computer Systems," Stanford University, SLAC-117, UC-32, May 1970.
5. Iuorno, R. F., et al., EADC/MULTICS Evaluation, RADC-TR-71-121, November 1971.
6. Lampson, B. W., "Dynamic protection structures," AFIPS Conf. Proc. 35, FJCC 1969, pp. 27-38.
7. La Padula, L. J., and D. Elliott Bell, "Harmonious Cooperation of Processes Operating on a Common Set of Data," Volumes 1, 2, and 3, ESD-TR-72-147, 1972.
8. Liskov, B. H., "The Design of the Venus Multiprogramming System," Comm ACM, 15, 3, March 1972, pp. 144-149.
9. Schroeder, M. D., and Jerome H. Saltzer, "A Hardware Architecture for Implementing Protection Rings," Comm ACM, 15, 3, March 1972.
10. Weissman, C, "Security Controls in the ADEPT-50 Time-sharing System," AFIPS Conf. Proc. 35, FJCC, 1969, pp. 119-133.

## BIBLIOGRAPHY

1. von Bertalanffy, Ludwig, General System Theory, George Braziller, Inc., New York, 1968.
2. Browne, P. S., and D. D. Steinauer, "A Model for Access Control," Proc. of 1971 ACM-SIGFIDEET Workshop, Data Description, Access and Control, 1971.
3. Conway, R., W. Maxwell, and H. Morgan, "Selective security capabilities in ASAP--A file management system," AFIPS Conf. Proc. 40, SJCC 1972.
4. Emerson, H., "An Approach to Handling Multi-Level Data Element Security Within a File," Proc. Invitational Workshop on Networks of Computers, Ad 860 776, October, 1968.
5. Friedman, T.D., "The authorization problem in shared files," IBM Sys. J., No. 4, 1970, pp. 258-280.
6. Graha\_, G. Scott, and Peter J. Denning, "Protection--Principles and practice (sic)," AFIPS Conf. Proc. 40, SJCC 1972, pp. 417-429.
7. Graham, R.M. "Protection in an information processing utility," Comm ACM, 15 May, 1968, pp. 365-369.



BIBLIOGRAPHY (Continued)

8. Hammer, Preston C., Ed., Advances in Mathematical Systems Theory, Pennsylvania State University Press, University Park, Pennsylvania, 1969.
9. Hoffman, L. J., "Computers and privacy: a survey," Computing Surveys, 1, 2, June, 1969, pp. 85-104.
10. Hoffman, L. J., "The Formulary Model for Access Control and Privacy in Computer System," Stanford University, SLAC-117, UC-32, May 1970.
11. Iuorno, R. F., et. al., RADC/MULTICS Evaluation, RADC-TR-71-121, November, 1971.
12. Klir, George J., An Approach to General Systems Theory, Van Nostrand Reinhold Company, 1969.
13. Klir, George J., ed., Trends in General Systems Theory, Wiley-Interscience, New York, 1972.
14. Lampson, B. W., "Dynamic protection structures," AFIPS Conf. Proc. 35, FJCC 1969, pp. 27-38.
15. Lampson, B. W., "On reliable and extendable operating systems," Techniques in software engineering, NATO Science Committee Working Material Vol. II, September, 1969.

BIBLIOGRAPHY (Concluded)

16. Lampson, B. W., "Protection," Proc. Fifth Annual Princeton Conf. on Inf. Sciences and Systems, Dept. of E. E., Princeton University, Princeton, N. J., March, 1971, pp. 437-443.
17. La Padula, L. J., and D. Elliott Bell, "Harmonious Cooperation of Processes Operating on a Common Set of Data," Volumes 1, 2, and 3, ESD-TR-72-147, 1972.
18. Liskov, B. H., "The Design of the Venus Multiprogramming System," Comm ACM, 15, 3, March, 1972, pp. 144-149.
19. Mesarović, M. D., D. Macko; and Y. Takahara, Theory of Hierarchical, Multilevel, Systems, Academic Press, New York, 1970.
20. Schroeder, M. D., and Jerome H. Saltzer, "A Hardware Architecture for Implementing Protection Rings," Comm ACM, 15, 3, March, 1972.
21. Weissman, C., "Security Controls in the ADEPT-50 Time-Sharing System," AFIPS Conf. Proc. 35, FJCC 1969, pp. 119-133.
22. Zadeh, L. A., and E. Polak, System Theory, McGraw-Hill Book Company, New York, 1969.